



AWK'23

WWW.AWK-AACHEN.DE 11th/12th of MAY 2023


Energy and Resource Efficiency in Manufacturing

Empower Green Production

Expert presentation – Session 2
Dr. Christoph Zeppenfeld

Companies have to provide evidence of their sustainability The pressure from politics and customers is growing

AWK'23



Current challenge: Limited willingness of customers to pay extra cost for sustainability

↔ Future: A change will come, preparation is necessary despite advance performance and payback risk

Companies must take action now to remain competitive

What measures need to be taken?

AWK'23

Short-term in manufacturing

time limit



Long-term in life phase

SCHAEFFLER



B+T
Unternehmensgruppe



MAN Energy Solutions
Future in the making

(Primary & Secondary)
Raw materials

Engineering

Material & Semi-
finished products

Product
manufacturing

Product use

Product
recycling

Products have different
life-cycles

Consumption through production

Material and consumption flows

Consumption in use phase

For the earth, it is the overall balance that counts – which is product-specific

4 steps on the way to more sustainable manufacturing: Target definition, measurability, measures IN and WITH manufacturing

AWK'23

Target

Strategic alignment



**Clear target definition
with
holistic consideration of
the value chain and
product life cycle!**

Measurability

Evaluability




*"You can't manage, what you don't
measure!" (P. Drucker)*

**What needs to be
measured?**

How can **sustainability** be
evaluated?

IN manufacturing

Short-term measures



WITH manufacturing

Life cycle assessment



Maximum sustainability
when considering the
**entire product life cycle/
-cycles**

- » Short-term measures to conserve resources and energy often located directly IN production
- » Great potential for long-term action to improve product sustainability WITH manufacturing

Transparency of consumptions in production are the basis for identifying levers to increase efficiency (I/II)


AMK'23

Create transparency


Visualize

Improve

Dashboard



Monitoring of energy peaks



— Energy consumption — Coated surface

Data Analysis

Use of an open source software to determine correlations and anomalies

- Reduction of peak loads
- Lower grid connection power required
- Higher supply security
- Alarm in the event of limit values being exceeded

Analysis of the causes of deviations → Levers for increasing efficiency





Transparency of consumptions in production are the basis for identifying levers to increase efficiency (II/II)

AMK'23

Create transparency

Visualize

Improve



- Production
- Ready for production
- Energy saving mode
- Start up

Annual energy savings of
28.7 GWh



Digital energy passport
for machines and plants




Lever of energy efficiency in machinery and equipment:
Expected 20 % savings in production through the digital energy passport

Energy efficiency at machine level

Design to meet requirements enables efficient operation


AWK'23

WITH the production of the machine **manufacturer**





The majority of CO₂-emissions from a machine tool occur during the use phase!

IN the production at the machine **user**




GMN



Savings potential of new machines: 46.9 % vs. previous machines

- 9.6 % - Optimization refrigeration equipment
- 8.0 % - Hydraulics (e.g.: DvP units)
- 6.9 % - Drive cooling with push-through technology
- 6.6 % - Reduction of sealing air, system pressure pneumatics
- 6.6 % - Stand-by-mode
- 3.2 % - IE3 motors




Energy efficiency at machine level

Design to meet requirements enables efficient operation


AWK'23

WITH the production of the machine **manufacturer**





+GF+

IN the production of the machine **user**



Potentials IN the product application (manufacturing of the machine user) are...

- » Often higher, but longer term
- » Frequently "recurring effects"
- » Tend to increase with rising costs (e.g. energy)



- 3.2 % - IE3 motors
- 6.6 % - Stand-by-mode
- 6.6 % - Reduction of sealing air, system pressure pneumatics
- 6.9 % - Drive cooling with push-through technology
- 8.0 % - Hydraulics (e.g.: DvP units)
- 9.0 % - Optimization refrigeration equipment


Energy efficiency at machine level

Optimization of the periphery: Lubricant supply system

AWK'23

System monitoring [4]


Energy consumption during rough grinding



Oil Reconditioning [18]

20% micro particles > 1 μm

80% nano particles < 1 μm



Nanoparticles are not separated by filters

Track grinding



$$A_{\text{Nozzle}} = 35 \text{ mm}^2 \quad \square \quad A_{\text{Nozzle}} = 18 \text{ mm}^2$$

~50 % saving

External cylindrical grinding




$$A_{\text{Nozzle}} = 100 \text{ mm}^2 \quad \square \quad A_{\text{Nozzle}} = 32 \text{ mm}^2$$

~ 62 % saving



RecondOil®

The RecondOil booster binds nanoparticles to form microparticles



CO₂ emissions ↓ 96 %

Scrap ↓ 1.3 %



OEE ↑ 1.6 %

Functional optimization through adaptation of manufacturing processes


Example: Sealing mating surfaces in the electric drive train

AWK'23

New challenges due to new technologies and product functionalities



Conventional manufacturing processes lead to leakage on electric motors at high speeds






Fulfillment of the increased product requirements for e-mobility through adaptation of the production technology (grinding of the seal mating surfaces) [6].

Material efficiency through technology substitution

Example: Plain bearings in wind turbines


AWK'23




In order to leverage potentials IN manufacturing, a change in the technologies can lead to success

The special position of manufacturing: In the middle of the chain

AWK'23




- 1) Emission reduction, resource reduction, cost reduction
- 2) Production Footprint (not everything is on the drawing)
 - Formation of peripheral zone
 - Surface structure
 - Tolerances ...



 Internal optimization cycles

The levers are located at different points in the product life cycle, depending on the environmental impacts

AWK'23



The potential lies in...

- » The material flows
- » The life cycles
- » Their dependencies

IN manufacturing

WITH manufacturing

Figure i. A. a [7]

Levers for improving sustainability in the product life cycle

Example: Acoustic absorber

AWK'23




Figure i. A. a [7]

carcoustics
more than silence!



» Shredding of production waste & use as filling material

» Improvement of the acoustic properties and thus the **component functionality**

IN manufacturing WITH manufacturing

Levers for improving sustainability in the product life cycle

Example: Coated screws

AWK'23




Figure i. A. a [7]



» Coating of the screws for longer life

» Emissions in production but savings due to longer shelf life



Levers for improving sustainability in the product life cycle

Example: marine engine

AWK'23




Figure i. A. a [7]



- » CO₂ emissions in own manufacturing approx. 120 t / engine
- » CO₂ emissions during operation: 70,000 t / year (18V4X), 30-year service life
- » Great leverage for efficiency increases through functionally appropriate components

IN manufacturing *WITH* manufacturing

Levers for improving sustainability in the product life cycle

Example: marine engine

AWK'23





Figure i. A. a [7]

§

Demands towards companies to improve their **sustainability** are increasing rapidly

🔍

The levers are product-specific: "**One size does not fit all**"

CO₂

Levers are located both "**IN**" and "**WITH**" manufacturing

€

The potentials are in the **bottom-line** (cost reduction) **AND** **top-line** (USPs for customer)

⚖️

The Trade-off between today's effort & costs and future payback


□ Investment in **long-term competitive advantage**

- [1] D. Frans, J. Rabe, Y. Ruf and D. Koroleva. "Six areas where companies can reduce their emissions. can reduce rapidly." <https://www.rolandberger.com/de/Insights/Publications/Mehr-Tempo-bei-der-Decarbonization.html> (accessed on: February 28, 2023).
- [2] G. Grünert, "CO2 balancing for grinding technology - challenges and opportunities".
- [3] J. Falker, "Spindle technology and digitization as enablers for more efficiency and sustainability in grinding".
- [4] R. Stabauer, "Minimizing the use of cooling lubricant in grinding".
- [5] D. Wilke, "Resource Saving and Quality Improvement through Innovative Oil Reconditioning".
- [6] T. Bergs, "Function-optimized grinding machining of drive components".
- [7] J. Lienig and H. Brümmer, "Recyclinggerechtes Entwickeln und Konstruieren," in Elektronische Gerätetechnik: fundamentals for developing electronic assemblies and devices, J. Lienig and H. Brümmer, eds, Berlin: Springer Berlin, 2014, pp. 193-218.



Dr.-Ing. Christoph Zeppenfeld

Head of Q | HSE | Sustainability
Group Quality | HSE | Sustainability
MAN Energy Solutions
86153 Augsburg
✉ christoph.zeppenfeld@man-es.com



Dr.-Ing. Sebastian Barth

Chief Engineer Technology Management
in Manufacturing and Grinding Technology
Werkzeugmaschinenlabor WZL of RWTH Aachen University
Campus Boulevard 30, D-52074 Aachen
☎ +49 241-28183
✉ S.Barth@wzl.rwth-aachen.de

We would like to thank the experts involved in the working group for their support:

Dr.-Ing. T. Augspurger, Makino Europe GmbH
Dr.-Ing. S. Bastürk, Schaeffler Technologies AG & Co. KG
F. Benner, B+T GmbH & Co. KG
Dr.-Ing. M. Duscha, Schaeffler Technologies AG & Co. KG
Dr.-Ing. D. Friedrich, Grindaix GmbH
G. Fuchs, BMW AG
Dr.-Ing. A. Heckl, Schaeffler Technologies AG & Co. KG
H. Johann, ZF Friedrichshafen AG
L. Johannsen, Carcoustics Shared Services GmbH
Dr.-Ing. M. Orth, igus GmbH
Dr. R. Perez, GF Machining Solutions GmbH
Dr.-Ing. T. Röthlingshöfer, EMAG Maschinenfabrik GmbH
J. Seele, GF Machining Solutions GmbH
Dr. Uwe Schleinkofer, Ceratizit Austria GmbH
Dr.-Ing. M. Terhorst, Carcoustics TechConsult GmbH
J. Wiese, WBA Aachener Werkzeugbau Akademie GmbH

Thank you very much for your attention!